

Specifications



Photo is representative



Eaton 219654

Eaton Moeller® series CI-K Insulated enclosure, for PKZ0, 160 x 100 x 130 mm, +rotary handle, black/grey

General specifications

PRODUCT NAME	Eaton Moeller® series CI-K Accessory Insulated enclosure
CATALOG NUMBER	219654
MODEL CODE	CI-K2-PKZ0-G
EAN	4015082196547
PRODUCT LENGTH/DEPTH	132 mm
PRODUCT HEIGHT	180 mm
PRODUCT WIDTH	100 mm
PRODUCT WEIGHT	0.415 kg
COMPLIANCES	CE
CATALOG NOTES	Additional cable insertion membrane as cable entry gland: 2 x in the rear wall and 1 x at the bottom.



Powering Business Worldwide

Product specifications

USED WITH	+L-PKZ0 (2 units), +NHI or AGM, +U or A, PKZM0-...
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL	Is the panel builder's responsibility.

Resources

BROCHURES	Brochure - CI-K small enclosures
DECLARATIONS OF CONFORMITY	UKCA CI.-PKZ.. Surface mounted enclosures and accessories PKZ
	CE CI.-PKZ.. Surface mounted enclosures and accessories PKZ
DRAWINGS	eaton-manual-motor-starters-enclosure-dimensions-121x041.eps
	121X019
	eaton-manual-motor-starters-enclosure-ci-k-accessory-dimensions-003.eps
	121X041 121X070
	eaton-manual-motor-starters-enclosure-ci-k-accessory-dimensions.eps
ECAD MODEL	eaton-manual-motor-starters-enclosure-ci-k-accessory-3d-drawing-003.eps
	121I087
INSTALLATION INSTRUCTIONS	ETN.CI-K2-PKZ0-G
MCAD MODEL	eaton-manual-motor-starters-ci-k2-k4-pkz-instruction-leaflet-il03402002z.pdf
	eaton-cadenas-path-ci k gehaeuse-assemblies-ci k2 pkz0 g asmtpl.prj
	DA-CS-ci k2 pkz0 g
	DA-CD-ci k2 pkz0 g
	eaton-cadenas-side view-ci k2 pkz0 g side.pra
eaton-cadenas-front view-ci k2 pkz0 g front.pra	

CONDUCTORS**10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH**

Is the panel builder's responsibility.

10.9.3 IMPULSE WITHSTAND VOLTAGE

Is the panel builder's responsibility.

10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL

Is the panel builder's responsibility.

FITTED WITH:Black-gray rotary knob
N and PE terminal**ENCLOSURE MATERIAL**

Plastic

AMBIENT OPERATING TEMPERATURE - MAX

70 °C

AMBIENT OPERATING TEMPERATURE - MIN

-25 °C

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID

0 W

HEAT DISSIPATION CAPACITY PDISS

12.5 W

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID

0 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)

0 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS

0 W

PRODUCT CATEGORY

Accessories

DEGREE OF PROTECTIONIP65
NEMA Other**MODEL**

Surface mounting

KNOCKOUTS2 x M25 (cable entry knockout at the bottom)
2 x M25 (cable entry knockout at the top)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

