



### Main

|                               |                                          |
|-------------------------------|------------------------------------------|
| Range of product              | Telemecanique Limit switches XC Standard |
| Series name                   | Standard format                          |
| Product or component type     | Limit switch                             |
| Device short name             | XCKP                                     |
| Sensor design                 | Compact                                  |
| Body type                     | Fixed                                    |
| Head type                     | Rotary head                              |
| Material                      | Plastic                                  |
| Body material                 | Plastic                                  |
| Head material                 | Zamak                                    |
| Fixing mode                   | By the body                              |
| Movement of operating head    | Rotary                                   |
| Type of operator              | Spring return without operating lever    |
| Type of approach              | Lateral approach, 2 directions           |
| Number of poles               | 2                                        |
| Contacts type and composition | 1 NC + 1 NO                              |
| Contact operation             | Snap action                              |

### Complementary

|                                              |                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical connection                        | Male connector M12, 4 pins                                                                                                                                                                                                                                                                                                                                             |
| Contacts insulation form                     | Zb                                                                                                                                                                                                                                                                                                                                                                     |
| Positive opening                             | With                                                                                                                                                                                                                                                                                                                                                                   |
| Positive opening minimum torque              | 0.25 N.m                                                                                                                                                                                                                                                                                                                                                               |
| Minimum torque for tripping                  | 0.1 N.m                                                                                                                                                                                                                                                                                                                                                                |
| Maximum actuation speed                      | 1.5 m/s                                                                                                                                                                                                                                                                                                                                                                |
| [Ie] rated operational current               | 3 A at 240 V, AC-15 conforming to EN/IEC 60947-5-1 appendix A<br>0.27 A at 250 V, DC-13 conforming to EN/IEC 60947-5-1 appendix A                                                                                                                                                                                                                                      |
| [Ithe] conventional enclosed thermal current | 3 A                                                                                                                                                                                                                                                                                                                                                                    |
| [Ui] rated insulation voltage                | 300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14<br>250 V (pollution degree 3) conforming to IEC 60947-1                                                                                                                                                                                                                                              |
| Maximum resistance across terminals          | 25 MOhm conforming to IEC 60255-7 category 3                                                                                                                                                                                                                                                                                                                           |
| [Uimp] rated impulse withstand voltage       | 2.5 KV conforming to IEC 60664<br>2.5 kV conforming to IEC 60947-1                                                                                                                                                                                                                                                                                                     |
| Short-circuit protection                     | 4 A cartridge fuse, type gG                                                                                                                                                                                                                                                                                                                                            |
| Electrical durability                        | 5000000 Cycles, DC-13, 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 Cycles, DC-13, 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Mechanical durability                        | 15000000 cycles                                                                                                                                                                                                                                                                                                                                                        |
| Width                                        | 31 mm                                                                                                                                                                                                                                                                                                                                                                  |
| Height                                       | 65 mm                                                                                                                                                                                                                                                                                                                                                                  |
| Depth                                        | 30 mm                                                                                                                                                                                                                                                                                                                                                                  |
| Net weight                                   | 0.125 kg                                                                                                                                                                                                                                                                                                                                                               |
| Terminals description ISO n°1                | (21-22)NC<br>(13-14)NO                                                                                                                                                                                                                                                                                                                                                 |

## Environment

|                                       |                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------|
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27                                            |
| Vibration resistance                  | 25 gn (f= 10...500 Hz) conforming to IEC 60068-2-6                                      |
| IP degree of protection               | IP66 conforming to IEC 60529<br>IP67 conforming to IEC 60529                            |
| IK degree of protection               | IK04 conforming to EN 50102                                                             |
| Electrical shock protection class     | Class II conforming to IEC 61140<br>Class II conforming to NF C 20-030                  |
| Ambient air temperature for operation | -25...70 °C                                                                             |
| Ambient air temperature for storage   | -40...70 °C                                                                             |
| Protective treatment                  | TC                                                                                      |
| Product certifications                | UL[RETURN]CSA[RETURN]CCC                                                                |
| Standards                             | IEC 60204-1<br>IEC 60947-5-1<br>CSA C22.2 No 14<br>EN 60204-1<br>UL 508<br>EN 60947-5-1 |

## Packing Units

|                              |       |
|------------------------------|-------|
| Unit Type of Package 1       | PCE   |
| Number of Units in Package 1 | 1     |
| Package 1 Height             | 15 cm |
| Package 1 Width              | 30 cm |
| Package 1 Length             | 40 cm |
| Package 1 Weight             | 86 g  |

## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |