




PV5AC20A22

Product	Crane Pendant Station	
Type	5 Hole	
Contact	1NO	
Current	I _e	4A (250V AC)
Usage Category	AC15	
Mechanical Life	Min Qty	1000000
Electrical Life	Min Qty	100000
Operating Frequency	On-Off/Hour	Mech. 900 Elec. 900
Insulation Voltage	U _i	300 V
Impulse Withstand Voltage	U _{imp}	2.5 kV
Dielectric Strength (Body-Contact)	2.500V AC	
Dielectric Strength (Contact-Contact)	1.500V AC	
Isolation Resistance	10 MΩ (500 V DC)	
Operating Temperature	-15 / + 80 °C	
Pollution Degree	3	
Protection Degree	IP65	
Contact Material	AgNi	
Cable Section	1.5-2.5 mm ²	
Screw Torque	1.5Nm	
Short Circuit Breaking Capacity	I _{cs}	1kA
Serial	PV Series	
Speed	Single Speed	
1.Hole	Key Selector	
Specifications	Aesthetic look and ergonomic usage with assistance of ABS reinforced material	
	Mechanical interlock	
	Single and double speed	
Standards / Certificates	TS EN 60947-5-1 UL 508 VDE 0660	



PV5AC20A22



Devre Şeması
3 ——— 4

TEK HIZ BEYAZ
Devre Şeması
3 ——— 4
1 ——— 2

TEK HIZ SİYAH
Devre Şeması
3 ——— 4
1 ——— 2

TEK HIZ BEYAZ
Devre Şeması
3 ——— 4
1 ——— 2

TEK HIZ SİYAH
Devre Şeması
3 ——— 4
1 ——— 2

